

RESIDENTIAL PRODUCTS



TRUCOMFORT™ VARIABLE SPEED

XV20i 4TTV0
Up to 22.00 SEER/14.00 EER†

- 2, 3, 4 & 5 ton
- Woven Spine Fin™ coil
- Variable-speed fan motor
- Swept fan blade
- Compressor sound insulator
- Climatuff® Variable Speed inverter compressor
- ComfortLink™ II capability
- Two-wire connections
- WeatherGuard™ Top

XV18 4TTV8
Up to 18.00 SEER/13.00 EER†

- 2, 3, 4 & 5 ton
- Woven Spine Fin™ coil
- Variable-speed fan motor
- Swept fan blade
- Compressor sound insulator
- Climatuff® Variable Speed inverter compressor
- ComfortLink™ II capability
- Two-wire connections

2-STAGE

XL18i 4TTX8
Up to 18.00 SEER†

- 2, 3, 4 & 5 ton
- Spine Fin™ coil
- Swept fan blade
- 2-stage Climatuff® compressor
- WeatherGuard™ Top

XR17 4TTR7
Up to 18.00 SEER†

- 2, 3, 4 & 5 ton
- Spine Fin™ coil
- 2-stage Climatuff® compressor

SINGLE STAGE

XR16 4TTL6
Up to 17.00 SEER†

- Low profile
- 1.5 – 5 ton
- Copper tube aluminum fin coil
- Climatuff® compressor

XL16i 4TTX6
Up to 17.00 SEER†

- 1.5 – 5 ton
- Spine Fin™ coil
- Swept fan blade
- Climatuff® compressor
- WeatherGuard™ Top

XR16 4TTR6
Up to 17.00 SEER†

- 1.5 – 5 ton
- Spine Fin™ coil
- Climatuff® compressor

XR14 4TTR4
Up to 16.00 SEER†

XR13 4TTR3
Up to 14.50 SEER†

3 PHASE

XR17 4TTA7
Up to 18.00 SEER

- 3, 4 & 5 ton
- Spine Fin™ coil
- 2-stage Climatuff® compressor

XR14 4TTA4
Up to 16.50 SEER†

XR13 4TTR3
Up to 14.50 SEER†

COMMON FEATURES:

- 3, 3.5, 4 & 5 ton
- Spine Fin™ coil



All Trane Outdoor Air Conditioners and Heat Pumps have a Base Limited Warranty of 5 years on the compressor, coil, and functional parts, except for 3-phase products, which have a Base Limited Warranty of 1 year.

QUESTIONS ABOUT WARRANTY?
CONTACT YOUR LOCAL TRANE REPRESENTATIVE.

HEAT PUMPS

TRUCOMFORT™ VARIABLE SPEED

XV20i 4TWV0
Up to 21.00 SEER/13.50 EER/10 HSPF†

- 2, 3, 4 & 5 ton
- Woven Spine Fin™ coil
- Variable-speed fan motor
- Swept fan blade
- Compressor sound insulator
- Climatuff® Variable Speed inverter compressor
- ComfortLink™ II capability
- Two-wire connections
- WeatherGuard™ Top

XV19 4TWL9
Up to 19.5 SEER/11.5 HSPF

- Low Profile
- 2, 3, 4 & 5 ton
- Variable-speed fan motor
- Swept fan blade
- Compressor sound insulator
- Copper tube aluminum fin coil
- Climatuff® Variable Speed inverter compressor
- ComfortLink™ II capability

XV18 4TWV8
Up to 18.00 SEER/13.50 EER/10

- 2, 3, 4 & 5 ton
- Woven Spine Fin™ coil
- Variable-speed fan motor
- Swept fan blade
- Compressor sound insulator
- Climatuff® Variable Speed inverter compressor
- ComfortLink™ II capability
- Two-wire connections

2-STAGE

XL18i 4TWX8
Up to 18.00 SEER/9.50 HSPF†

- 2, 3, 4 & 5 ton
- Spine Fin™ coil
- Swept fan blade
- 2-stage Climatuff® compressor
- WeatherGuard™ Top

XR17 4TWR7
Up to 17.50 SEER/9.60 HSPF†

- 2, 3, 4 & 5 ton
- Spine Fin™ coil
- 2-stage Climatuff® compressor

SINGLE STAGE

XR16 4TWL6
Up to 17.00 SEER†/10 HSPF

- Low profile
- 1.5 – 5 ton
- Copper tube aluminum fin coil

XL16i 4TWX6
Up to 17.00 SEER/9.60 HSPF†

- 1.5 – 5 ton
- Spine Fin™ coil
- Swept fan blade
- Climatuff® compressor
- Compressor sound insulator (select models)
- WeatherGuard™ Top

3 PHASE

XR17 4TWA7
Up to 17.50 SEER/9.60 HSPF

- 3, 4 & 5 ton
- Spine Fin™ coil
- 2-stage Climatuff® compressor

XR14 4TWA4
Up to 15.50 SEER/9.50 HSPF

- 3, 3.5, 4 & 5 ton
- Spine Fin™ Coil

XR16 4TWR6
Up to 17.00 SEER/9.60 HSPF†

COMMON FEATURES:

- 1.5 – 5 ton
- Spine Fin™ coil
- Climatuff® compressor
- Compressor sound insulator (select models)

XR15 4TWR5
Up to 15.75 SEER/9.50 HSPF†

XR14 4TWR4
Up to 14.50 SEER/8.50 HSPF

90% + AFUE CONDENSING

XC95m TUHM / TDHM
COMMUNICATING
Up to 97.3% AFUE

- 60 – 120 mbth input
- ComfortLink™ II capability
- Fully modulating gas valve
- Three-wire connections
- Variable-speed communicating ECM blower motor
- Continuous Comfort-R™ mode
- Single or two pipe vent options
- Digital user interface for easy set up and diagnostics
- Silicon nitride igniter
- Variable-speed draft inducer
- Certified to 2% air leakage
- ENERGY STAR® qualified

S9V2-VS
Up to 97% AFUE

- Variable-speed ECM blower motor
- Comfort-R™ mode
- Compatible with 1-stage, 2-stage, and variable speed* OD equipment
- Variable speed draft inducer

S9V2
96% AFUE

- Variable-speed ECM blower motor
- Comfort-R™ mode
- Compatible with 1-stage, 2-stage, and variable speed* OD equipment
- Two-speed draft inducer

S9X2
Up to 96% AFUE

- Compatible with 2 stage OD equipment
- High efficiency 9 tap Constant Torque ECM blower
- Two-speed draft inducer

COMMON 2-STAGE S-SERIES FEATURES INCLUDED

- 40 – 120 mbth input
- Two-stage heat
- Single or two pipe vent options
- Fully insulated/gasketed
- Dry contact Humidifier and EAC terminals
- Silicon nitride igniter
- Standard 34" height
- Certified to 1% air leakage
- IFC board with digital configuration, status, and fault codes
- ENERGY STAR® qualified

S9X1
Up to 96% AFUE

- 40 – 120 mbth input
- Single-stage heat
- High efficiency 9 tap Constant Torque ECM motor
- Single-speed draft inducer
- Silicon nitride igniter
- Fully insulated/gasketed
- Single or two pipe vent options
- IFC board with digital configuration, status, and fault codes
- ENERGY STAR® qualified
- Certified to 1% air leakage

L9X1†
95% AFUE

- 50 & 100 mbth input
- Single-stage heat
- High efficiency 9 tap Constant Torque ECM blower
- 14 ng/J operation
- Silicon nitride igniter
- Fully insulated cabinet
- † California Only

S9B1
92.1% AFUE

- 40 – 120 mbth input
- Single-stage heat
- 9 tap Constant Torque ECM blower motor
- Single-speed draft inducer
- Silicon nitride igniter
- Single or two pipe vent options
- Stainless steel heat exchanger

80% AFUE NON-CONDENSING

XC80 TUD2-V / TDD2-V
COMMUNICATING

- 60 – 140 mbth input
- ComfortLink™ II
- Continuous Comfort-R™ mode
- Two-stage heat
- Three-wire connections
- Two-speed draft inducer
- Silicon nitride igniter
- Simplified Trane CleanEffects™ connections
- Variable-speed communicating ECM blower motor
- Digital user interface for easy set up and diagnostics
- Certified to 2% air leakage

XV80 TUD2-9V / TDD2-9V

- 60 – 140 mbth input
- Two-stage heat
- Variable-speed ECM blower motor
- Comfort-R™ mode
- Two-speed draft inducer
- Silicon nitride igniter
- Fully insulated/gasketed
- Factory wired for humidifier and EAC
- Certified to 2% air leakage

S8X2

- 40 – 140 mbth input
- Two-stage heat
- High efficiency 9 tap Constant Torque ECM blower
- Two-speed draft inducer
- Silicon nitride igniter
- Fully insulated**/gasketed
- Aluminized steel heat exchanger
- Compatible with Trane CleanEffects™

S8X1

- 26 – 120 mbth input
- Single-stage heat
- High efficiency 9 tap Constant Torque ECM blower
- Single-speed draft inducer
- Silicon nitride igniter
- Fully insulated**/gasketed
- Humidifier & EAC terminals
- Certified to 1% air leakage

L8X1†

- 55 - 100 mbth input
- Single-stage heat
- 5 tap Constant Torque ECM blower
- 14 ng/J operation
- Silicon nitride igniter
- Fully insulated cabinet
- † California Only

S8B1

- 26-120 mbth input
- Single-stage heat
- 9 tap Constant Torque ECM blower
- Single-speed draft inducer
- Silicon nitride igniter
- Certified to 1.4% air leakage

*Relay panel required when matched with variable speed outdoor units
**14.5" models do not contain blower compartment insulation



QUESTIONS ABOUT WARRANTY?
CONTACT YOUR LOCAL TRANE REPRESENTATIVE.

† ENERGY STAR® qualified system ratings available for select models.

COILS

CASED MULTI-POSITION



4TXC

- Single, 2-stage and variable speed equipment
- TXV (heat pump capable)
- Enhanced fin design for efficiency and humidity control
- Double-sloped high temp drain pan
- All-Aluminum to prevent formicary corrosion



4MXC

- Single stage equipment only
- Fixed orifice
- TXV kit available for expanded ratings and applications
- All-aluminum to prevent formicary corrosion



4PXC-D / 4PXC-U

- U = Upflow/Downflow*
D = Downflow only**
(Optimized for downflow efficiency and ratings)
- Single, 2-stage and variable speed equipment
 - TXV (heat pump capable)
 - Double-sloped high temp drain pan
 - Enhanced fin design for efficiency and humidity control
 - All-aluminum to prevent formicary corrosion

UNCASED



4PXA


- TXV (heat pump capable)
- Double-sloped high temp drain pan
- Enhanced fin design for efficiency and humidity control
- All-aluminum to prevent formicary corrosion

CASED



4PXF

- Single, 2-stage and variable speed equipment
- TXV (Heat pump capable)
- High temp drain pan
- Copper/Aluminum



All Trane Coils have a Base Limited Warranty of 5 years on the internal functional parts.

QUESTIONS ABOUT WARRANTY?
CONTACT YOUR LOCAL TRANE REPRESENTATIVE.

*Convertible to horizontal left or right with kit. **Convertible to horizontal right with kit.

AIR HANDLERS

HYPERION™ AIR HANDLERS



TAM9

- ComfortLink™ II or 24V Operation
- 2 – 5 ton
- Continuous Comfort-R™ mode
- Composite Vortica™ blower housing
- All-aluminum coil
- Double wall modular cabinet
- Multi-position installation
- Side return option
- Electronic expansion valve
- Variable-speed ECM blower motor
- 2% air leakage models available (Meets R4.2 requirements)



GAM5

- 1.5 – 5 ton
- High efficiency four-speed ECM blower motor
- Composite Vortica™ blower housing
- All-aluminum coil
- Double wall modular cabinet
- Multi-position installation
- Side return option
- R-410A TXV
- 2% air leakage models available (Meets R4.2 requirements)



GAF2

- 1.5 – 3 ton
- PSC three-speed blower motor
- Composite Vortica™ blower housing
- All-aluminum coil
- Double wall cabinet
- Three-way conversion
- Front return option
- 2% air leakage models available (Meets R4.2 requirements)

CONVERTIBLE



TEM8

- ComfortLink™ II or 24V Operation

COMMON FEATURES FOR TEM8 AND TEM6:

- 2 – 5 ton
- Variable-speed ECM blower motor
- All-aluminum coil
- R-410A TXV
- Multi-position installation

TEM6

- Metal Vortica™ blower
- Galvanized steel metal cabinet
- 2% air leakage models available (Meets R4.2 requirements)

TEM4

- 1.5 – 5 ton
- ECM motor on select models
- PSC three-speed blower motor
- Metal Vortica™ blower
- All-aluminum coil
- Galvanized steel metal cabinet
- R-410A TXV
- Multi-position installation
- 2% air leakage models available (Meets R4.2 requirements)

UPFLOW



TMM5

- 2 – 3 ton
- Upflow, Front and Bottom Return
- ECM blower motor
- R-410A TXV
- Galvanized steel metal cabinet
- 2% air leakage models available (Meets R4.2 requirements)
- All-aluminum coil

TMM4

- 1.5 – 3 ton
- Upflow, Front and Bottom Return
- Fixed orifice
- Optional TXV kit
- Multi-speed PSC blower motor
- Galvanized steel metal cabinet
- 2% air leakage models available (Meets R4.2 requirements)
- All-aluminum coil



Trane TAM9, TEM8, TEM6, TEM4, GAF2, and GAM5 Indoor Air Handlers have a Base Limited Warranty of 10 years on the coil and other internal functional parts. TMM4, and TMM5 Indoor Air Handlers have a Base Limited Warranty of 3 years on the coil and other internal functional parts.

QUESTIONS ABOUT WARRANTY?
CONTACT YOUR LOCAL TRANE REPRESENTATIVE.

IAQ (INDOOR AIR QUALITY)

TRANE CLEANEFFECTS™



TFD

- Up to 100 times more effective than a standard 1" throwaway filter
- Power door provides easy access to internal components and features a filter status display as well as safety interlocks that automatically shut down the power when the door is opened for maintenance or cleaning
- Removes up to 99.98% @.3 Micron size allergens from the filtered air
- ComfortLink II™ communicating or 24 volt capability
- Allergy and Asthma Friendly® Certified
- Quiet operation

QUIKBOX



EQBFM

- MERV 11 Media Filter
- Quick shirt box type design
- Stores flat, installs in seconds
- 11 sizes to match most cabinet widths
- Backward compatible for all Perfect Fit (TFM) filter boxes
- New smaller cabinet to meet competitive brands
- Low pressure drop; up to 6 mos. lifecycle

SLIMFIT FILTER



BAYSF 1165, 1185, 1235, 1265

- 1" Pleated Filter, MERV 4 rated, lasts up to 90 days
- Made-to-fit cabinet sizes for TEM Air Handlers and S9V and S9X furnace side return cabinets
- 2" depth low profile painted steel cabinet with hinged door for easy filter replacement

EVAPORATIVE HUMIDIFIERS



EHUMD500

- FAN POWERED
- Capacity: 18 gallons per day
 - Sq. Ft. Capacity: Up to 4,200
 - Unit Type: Power humidifier/automatic control



EHUMD300

- LARGE BYPASS
- Capacity: 16.8 gallons per day
 - Sq. Ft. Capacity: Up to 4,000
 - Unit Type: Large bypass humidifier/automatic control

EHUMD200

- SMALL BYPASS
- Capacity: 12 gallons per day
 - Sq. Ft. Capacity: Up to 3,000
 - Unit Type: Small bypass humidifier/manual control



EHUMD800

- Capacity: 11 – 34.6 gallons per day
- Sq. Ft. Capacity: Up to 5,000

EHUMD800LC

- For 120V applications only
- For low conductivity water applications
- Up to 11 gal. per day output
- Replaceable LC canister available

VENTILATION



EDHUM70V

- Automatically energizes compressor when entering air is above enthalpy set point
- 62.2 Compliant Ventilator and Dehumidifier in one product
- Ventilation up to 125 cfm - sized for a 4BR, 3000 sq.' home
- Up to 70 ppd moisture removal in dehumidification mode
- MERV 11 Filter included
- Dedicated Thermostat or Trane enabled Smart thermostat



EERV100 EERV200 EERV300

COMMON FEATURES:

- 1.5 – 5 ton
- Spine Fin™ coil
- Climatuff® compressor
- Compressor sound insulator (select models)



EVENQF130V


- 62.2 Compliant Ventilation
- Full ECM Motor with Intelligent Logic Controller
- Adjustable airflow from 40 to 130 cfm to meet ventilation codes for all size homes
- 24V functionality from a smart thermostat, or use the on-board controller for "set-it and forget it" installation
- MERV 8 filter included for improved IAQ

DEHUMIDIFIER



EDHUM

- Energy Star rated
- Exclusive XT coil technology means higher efficiency humidity removal rates than standard units
- Optional ventilation capability to meet ASHRAE 62.2 requirements
- Can be ducted to and wired to operate with HVAC system or can used independently of HVAC system with internal blower and wired control
- MERV 11 Filter included



Envirowise™ CleanEffects, Evaporative Humidifiers, Steam Humidifiers and TERV100/200/300 have a Base Limited Warranty of 5 years on the internal functional parts. The Quikbox and Slimfit Filters not included. Trane EDHUM70V, EDHUM and QF130V have a Base Limited Warranty of 1 year.

QUESTIONS ABOUT WARRANTY?
CONTACT YOUR LOCAL TRANE REPRESENTATIVE.

COMFORTLINK™ II CONNECTED CONTROLS



XL1050 TZON1050

- ComfortLink™ II communications
- ComfortLink™ II zoning
- Compatible with 24 volt systems*
 - 5 heat / 2 cool
 - Remote ID, OD sensor connections
- Remote Climate Access included
- Built in Bridge for Z-Wave devices
- Connect over 200 Z-Wave devices
- Trane Diagnostics ready
- WiFi (802.11 b/g/n) or Ethernet connection
- Control from a smartphone, tablet, or computer
- 7" diagonal color HD display
- 1-touch presets – Home, Away, Sleep
- 7-day programmable with up to four schedules per day
- Customizable home screen



XL850 TCONT850

- Remote Climate Access included**
- Built in Bridge for Z-Wave devices
- ComfortLink™ II communications
- Wi-Fi or Ethernet Connectivity
- Trane Diagnostics ready
- Compatible with 24 volt systems*
- 5 heat / 2 cool
- 7-day programmable with up to 4 periods/day
- 4.3" color display
- Dual Fuel Capable
- 2 filter change reminders
- 5-day weather forecast, local radar & alerts
- Allergy and quick clean cycles
- Ventilation control*
- Maintenance reminders
- Customizable home screen
- Embedded diagnostics
- Color: Designer Silver



CONNECTED CONTROLS



XR724 TCONT724

- Remote Climate Access included**
- Wi-Fi Connectivity
- 4 heat/2 cool
- Z-Wave Connectivity****
- Trane Diagnostics ready
- 4.3" diagonal LCD touchscreen
- Screen lock out and guest lock out
- Built-in humidity sensor
- Dehumidification setting
- Dual Fuel capable
- Filter, maintenance and humidifier service reminder alerts
- Color: Silver



XL1040 TZON1040

- ZONING COMMUNICATING SENSOR WITH DISPLAY
- For use with ComfortLink™ II Zoning Systems
 - 3-Wire Communicating Zone Sensor
 - 4.3" diagonal color touchscreen
 - Zone Mode - Auto only
 - Fan Mode - Auto/On
 - Displays Zone Temperature & Relative Humidity.
 - Average multiple zone temp sensors
 - Displays Outdoor Temperature (Trane Home™ registration or wired ODT required)
 - Clean Screen Function
 - 3 Levels of Restricted Access
 - Fahrenheit or Celcius
 - Adjust zone Setpoint at 1040, 1050, and from the Trane Home™ app
 - Schedule 1040, 1050 from the Trane Home app
 - Zone Schedule Override – Permanent Hold
 - Enter zone name at 1040 and 1050
 - Local software upgrades
 - Screen color with backlit options
 - Screen saver options

XL824 TCONT824

- ENERGY STAR® certified
- Remote Climate Access included**
- Wi-Fi or Ethernet connectivity
- Built in Bridge for Z-Wave devices
- Trane Diagnostics ready
- Used with conventional 24 volt systems
- 5 heat / 2 cool
- 7-day programmable
- 4.3" color display
- 2 aux dry contacts***
- Humidity sensor
- Humidifier, ventilation, and dehumidifier control
- 2 filter change reminders
- 5-day weather forecast, local radar & alerts
- Dual Fuel capable
- Allergy and quick clean cycles
- Maintenance reminders
- Customizable home screen
- Embedded diagnostics
- Smart continuous fan
- Color: Designer Silver

SENSORS



ZZSENSAL 0400

- WIRED INDOOR TEMPERATURE SENSOR
- Indoor sensor for use with TZON1050, TCONT402A, TCONT624, TCONT824, TCONT850

BAYSENS01

- WIRED OUTDOOR TEMPERATURE SENSOR
- Outdoor sensor for use with TZONE950, TZON1050, TCONT401A, TCONT402A, TCONT624, TCONT824, TCONT850



ZSENS930

- INDOOR WIRELESS TEMPERATURE AND HUMIDITY SENSOR
- Z-Wave device
 - Monitor through Trane® Home mobile app
 - Integrates with built-in Bridge of TZON1050, TCONT824, TCONT850



Trane XL1050, XL940, XL850, XL724, and XL824 Controls have a Base Limited Warranty of 5 years on the internal functional parts. The Trane XR724 and ZSENS930 have base limited warranty of 1 year on the internal functional parts.

QUESTIONS ABOUT WARRANTY?
CONTACT YOUR LOCAL TRANE REPRESENTATIVE.

*BAY24VRPAC52DC Relay Panel required.

**Complimentary service for up to 8 professionally installed connected controls. Complimentary service includes up to 1 lighting or appliance module per control (maximum 8) installed. Unlimited Trane® Home Wi-Fi cameras (live streaming only) is included with complimentary Trane® Home remote climate access. Cameras and lighting controls are optional purchase.

***Auxiliary dry contacts may be configured to control 1) whole house humidifier; 2) dehumidifier; 3) ventilation system.

****Requires Z-Wave Bridge, purchase separately to connect to Trane Home Mobile App.

7-DAY OR 5/1/1 PROGRAMMABLE



XR303 TCONT303

- 4 heat/2 cool
- Humidity sensor
- Dual fuel capable

COMMON FEATURES

- 5" Inteactive touch screen
- Auto changeover
- Real-time clock

XR302 TCONT302

- 4 heat/2 cool
- Dual fuel capable

- Large back lit display
- Armchair programming
- Air filter reminder



XR203 TCONT203

- 4 heat/2 cool
- Dual fuel capable

COMMON FEATURES

- 3.5" Diagonal Backlit Display
- Simple programming
- Standard wiring terminal block
- Simultaneous display
- Soft key controls



XR202 TCONT202

- 1 heat/1 cool

NON-PROGRAMMABLE



XR103 TCONT103

- 2 heat/1 cool HP only
- Configurable Switchover Valve
- Emergency Heat
- Common required

COMMON FEATURES

- Push Button, Non-Programmable
- 1.9" Diagonal Display
- Fahrenheit or Celcius



XR102 TCONT102

- Up to 1 heat/1 cool
- No Common Terminal
- Battery Powered Only



Trane XR303, XR302, XR203, XR202, XR103 and XR102 Thermostats have a Base Limited Warranty of 1-Year on the internal functional parts.

QUESTIONS ABOUT WARRANTY?
CONTACT YOUR LOCAL TRANE REPRESENTATIVE.

SENSORS



ZZSENSAL0300

- WIRED INDOOR TEMPERATURE SENSOR
- Indoor sensor for use with TCONT303, TCONT302

BAYSEN30ATEMPA

- WIRED OUTDOOR TEMPERATURE SENSOR
- Outdoor sensor for use with TCONT303, TCONT302

PACKAGED

COOLING



XL15c 4TCY5

15.00 SEER

- 2 - 5 ton
- Variable-speed indoor blower motor
- Comfort-R™ mode
- Spine Fin™ condenser
- Single phase only
- Climatuff® compressor
- Composite Vortica™ blower
- Ultra quiet
- Compatible with CleanEffects™

XL14c 4TCY4

Up to 14.25 SEER

- 3 - 5 ton
- Variable-speed indoor blower motor
- Comfort-R™ mode
- Spine Fin™ condenser
- Three phase only
- Climatuff® compressor
- Composite Vortica™ blower
- Ultra quiet
- Compatible with CleanEffects™



XR14c 4TCC4

14.00 SEER

- 2 - 5 ton
- Climatuff® Compressor
- Spine Fin™ condenser
- Single phase
- Composite Vortica™ blower
- Microchannel evaporator coil on 2 - 4 ton
- Compatible with CleanEffects™

HEAT PUMPS



XL16c 4WCZ6

Up to 16.00 SEER/8.50

- 2, 3, 4 & 5 ton
- 2-stage Climatuff® compressor
- Variable-speed indoor blower motor
- Comfort-R™ mode
- Composite Vortica™ blower
- Single and 3-phase
- Tough corrosion and UV resistant paint
- Demand defrost
- Ultra quiet
- Compatible with CleanEffects™

XL15c 4WCY5

15.00 SEER/8.20 HSPF

- 2 - 5 ton
- Climatuff® compressor
- Variable-speed indoor blower motor
- Single phase only
- Composite Vortica™ blower
- Tough corrosion and UV resistant paint
- Demand defrost
- Ultra quiet
- Compatible with CleanEffects™



XR14c 4WCC4

14.00 SEER/8.00 HSPF

- 2 - 5 ton
- Climatuff® Compressor
- Spine Fin™ condenser
- Tough corrosion and UV resistant paint
- Composite Vortica™ blower
- Single phase only
- Demand defrost
- Compatible with CleanEffects™



XR14h 4WHC4

OVER/UNDER
14.00 SEER/8.00 HSPF

- 2 - 3.5 ton
- Single phase only
- DuraTuff™ outdoor plate fin coil
- Direct drive two-speed blower motor
- Compatible with CleanEffects™

GAS/ELECTRIC



XL16c 4YCY6

Up to 16.00 SEER/81% AFUE

- 2*, 3, 4 & 5 ton
- 2-stage Climatuff® compressor
- 2-stage gas heat
- Variable-speed indoor blower motor
- Composite Vortica™ blower
- Comfort-R™ mode
- Spine Fin™ condenser
- Single and 3-phase
- Tough corrosion and UV-resistant paint
- All stainless steel heating system
- Ultra quiet
- Compatible with CleanEffects™

XL15c 4YCY5

Up to 15.00 SEER/81% AFUE

- 2 - 5 ton
- 2-stage gas heat
- Climatuff® compressor
- Variable-speed indoor blower motor
- Composite Vortica™ blower
- Comfort-R™ mode
- Spine Fin™ condenser
- Ultra quiet
- Tough corrosion and UV resistant paint
- Single phase only
- All stainless steel heating system
- Compatible with CleanEffects™

XL14c 4YCY4

14.30 SEER/80% AFUE

- 3 - 5 ton
- Climatuff® compressor
- Spine Fin™ condenser
- Composite Vortica™ blower
- All stainless steel heating system
- Tough corrosion and UV-resistant paint
- Three Phase Only
- Compatible with CleanEffects™



XR14c 4YCC4

14.00 SEER/81% AFUE

- 2 - 5 ton
- Climatuff® Compressor
- Spine Fin™ condenser
- Composite Vortica™ blower
- All stainless steel heating system
- Tough corrosion and UV resistant paint
- Microchannel evaporator coil on 2 - 4 ton
- Single phase only
- Compatible with CleanEffects™

3 PHASE



XL14c 4WCY4

14.25 SEER/8.00 HSPF

- 3-5 ton
- Climatuff® compressor
- Variable-speed indoor blower motor
- Three phase only
- Composite Vortica™ blower
- Tough corrosion and UV-resistant paint
- Demand defrost
- Ultra quiet
- Compatible with CleanEffects™

EARTHWISE™ HYBRID DUAL FUEL



XL16c 4DCZ6

Up to 16.00 SEER

- 3, 4 & 5 ton
- 2-stage Climatuff® compressor
- Variable-speed indoor blower motor
- Spine Fin™ condenser
- Comfort-R™ mode
- Composite Vortica™ blower
- Single and 3-phase
- Heat pump and/or 2-stage gas heat operation
- All stainless steel heating system
- Ultra quiet
- Compatible with CleanEffects™

XL14c 4DCY4

14.00 SEER

- 2 - 5 ton
- Climatuff® compressor
- Variable-speed indoor blower motor
- Single and 3-phase
- Spine Fin™ condenser
- Comfort-R™ mode
- Heat pump and/or 2-stage gas heat operation
- Composite Vortica™ blower
- All stainless steel heating system
- Ultra quiet
- Compatible with CleanEffects™



All Trane Packaged systems have a Base Limited Warranty of 5 years on the compressor, coil, and functional parts. Gas/Electric and Earthwise Hybrid Dual Fuel systems have a Base Limited Warranty of 20 years on the heat exchanger.

QUESTIONS ABOUT WARRANTY? CONTACT YOUR LOCAL TRANE REPRESENTATIVE.



All trademarks referenced are the trademarks of their respective owners.

About Trane

Trane - by Trane Technologies (NYSE: TT), a global climate innovator - creates comfortable, energy efficient indoor environments for commercial and residential applications. For more information, visit Trane.com or TraneTechnologies.com

© 2021 TRANE. ALL RIGHTS RESERVED. 62-1014-31 05/21